

TECHNICAL FEATURES - Koleos MY 2021

ENGINE	TCe 160 EDC GPF	Blue dCI 190 X-Tronic All Mode 4x4-i		
Fuel	Gasoline	Diesel		
Pollution control standard	Euro6 D-Full	Euro6 D-Full		
Protocole d'homologation	WLTP	WLTP		
Fiscal capacity	8	10		
Cubic capacity (cm3)	1333	1997		
Number of cylinders / valves	4/16	4 / 16		
Maximum output kW CEE (hp) / rpm	116 kW / 5500 rpm	135 kW / 3500 rpm		
Maximum torque Nm CEE (m.kg) / rpm	270 Nm / 1800-3750 rpm	380 Nm / 1750 - 3250 rpm		
distribution type	Chain	Chain		
Injection	direct petrol injection	Common-Rail		
Exhaust treatment system	catalytic converter with petrol particle filter	diesel particulate filter with Nox post-treatment via urea solution		
TRANSMISSION	7-Speed automatic gearbox with double clutch (EDC)		X-Tronic	
Gearbox	EDC	CVT 4WD		
Number of speed	7	CVT		
PERFORMANCES				
SCx	0,892 m ² ▯	0.895 m ²		
Maximum speed (km / h)	200 km/h	198		
400 m Departure stopped (s)	17.0 s	17,1		
1000 m (s)	31.2 s	31,3		
0-100 km / h (s)	7.5 s	10,2		
Takeover : 80 km / h - 120 km / h (s) en 4e / 5e	7.6s	8		
CONSUMPTION & EMISSIONS				
CO2 (g / km)	153	182		
Mix (l/100 km)	6,762	6,943		
Fuel tank capacity (l)	60	60		
Urea tank capacity (l)	-	16.4 L		
GROUND CONNECTION - STEERING AND SUSPENSIONS				
Front suspension	Pseudo McPherson with lower wishbone, coil spring suspension with hydraulic telescopic shock absorbers and anti-roll bar	Pseudo McPherson with lower wishbone, coil spring suspension with hydraulic telescopic shock absorbers and anti-roll bar		
Rear suspension	Multilink	Multilink		
Steering	Electric power steering	Electric power steering		
Turning diameter between kerbs (m)mesure officielle	11,9	11,9		
Number of steering wheel turns between stops	3,047	3,047		
BRAKING				
Front:	Ventilated disc Ø296x26	Ventilated disc Ø320x28		
Rear:	Ventilated disc Ø292x16	Ventilated disc Ø292x16		
Electronic brake splitter	Yes	Yes		
ABS	Yes	Yes		
Emergency Brake Assist System	Yes	Yes		
Electronic stability control - ESC	Yes	Yes		
WHEELS & TYRES				
Tyres	225 / 55 R19	225 / 65 R17	225 / 60 R18	225 / 55 R19
Spare wheel	Inflation kit	Inflation kit		
WEIGHTS (kg)				
Tare mass	1608	1866		
Payload	560	560		
Max. total permissible load	2075	2333		
Permissible total rolling mass	3725	4333		
Maximum towable braked mass (12% slope)	1650	2000		
Unbraked maximum towable mass	750	750		
Max. roof load (kg)	80	80		